

THE SACK FILLING & ROBOT PALLETISING COMPANY

LIMITED



$\mathbf{T5000}$

Specially designed to fill a wide range of granular or fibrous materials into open mouthed bags and containers. Unique fill by weight or volumetric fill bagging units form the center piece of fast and accurate pre-pack lines for maximum output with minimum labor.

- Quick realse pneumatic bag clamps for all types of open mouth sacks.
- Variable speed control feed belt to optimise throughput
- Pneumativally assisted trickle feed system offers, rapid and simple adjustment for varying products.

T5000 Fill by weight version

Suitable for use with most granular and fibrous materials. Weight range between 10kg - 50kg.

T5000 Fill by volume version

Suitable for use with peat, composts, bark, bio-humus and other fibrous materials. Built in possing action to settle material into the bag. Volume range between 10 - 100 litres.

Optional Extras

- Stainless steel construction for food quality
- Sealed belt for dusty materials.
- Dust extraction points
- Range of automatic sack placers, conveyor, sealing systems and hoppers from The Sack Filling range



TECHNICAL SPECIFICATIONS Throughput

Up to 500 bags per hour (depending on produce and bag size)

Weight Range

T5000 weight range: 10kg to 50kg. T5000 volume range: 10-100 litres.

Pneumatic Requirement

T5000 : 145 litres/min @ 5.5bar /80psi T5000 : 280 litres/min @ 5.5bar/80psi

Electrical Requirement

T5000 : 415VAC 3ph T5000 : 415VAC 3ph & N

After Sales Service

Fast on site service by factory trained engineers coupled with extensive stocks of competitively priced spare parts guarantees maximum productivity and protects the customer's investment.



The Sack Filling & Robot Palletising Company Ltd. Walthambury House, Cressing Farm Witham Road, Cressing Essex CM77 8PD

Tel: +44 (0)1376 552020 E-Mail: sales@sfrpc.co.uk www.thesackfillingandrobotpalletisingcompany.co.uk



THE SACK FILLING & ROBOT PALLETISING COMPANY